



Technical specifications

Product	CoRe+ Max
Aluminum casing	RPWT  
Charging connector	SAE J1772
Cable	7.62 m / 25'
Input	208 VAC or 240 VAC for each charging station
Charging power	1.2 kW to 19.2 kW (maximum configurable by software)
Output current	6A to 80A (maximum configurable by software and adjustable via a rotary switch)
Integrated GFCI	20 mA, auto reset (3 attempts at 15-minute intervals)
Frequency	60 Hz
Operating and storage temperature	-40 °C to 50 °C / -40 °F to 122 °F
Weight	Charging station: 9.5 kg / 27 lb Pedestal: 14.5 kg / 32 lb
Humidity	Up to 95% (non-condensing)
Card reader	ISO 14443 A/B, ISO 15693, NFC
Communication interface	ZigBee - IEEE 802.15.4 meshed network
Networking	Cellular – 4G/LTE (gateway is installed separately for optimal performances)
Pending Certifications	CSA - C22.2 No. 280 / UL 2594, CSA C22.2 No 281.1 and 281.2 / UL 2231-1 and 2231-2
EMI compliance	USA - FCC 47 CFR part 15 class A CAN - ICES-003 (A)



Learn more
info@flo.com
 1 855 543-8356
flo.com/products



Designated and manufactured
 by AddÉnergie Technologies Inc.